

**DEXRON® Aluminum Beaker Oxidation Test  
Report Form  
Form 1  
Version**

Formulation Code							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Count	Method	Lab	Instrument

Blended Sample Testing Information <sup>A</sup>			
Candidate Percentage			Other Percentage
Other Fluid ID			

<sup>A</sup> If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and "None" for Blend Fluid ID.

Test Identification			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number <sup>B</sup>			
Instrument		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	

<sup>B</sup> Test Number = Instrument – Run Number

Test Validity Statement	
This test has been conducted in a valid manner – YES or NO	
Test Laboratory	
Signature	
Typed Name	
Title	

**DEXRON® Aluminum Beaker Oxidation Test  
Pass/Fail Results  
Form 2**

Formulation Code	
Test Number	

<b>PASS/FAIL RESULTS</b>		
<b>PARAMETERS</b>	<b>UNITS</b>	<b>RESULTS</b>
Pentane Insolubles Weight %	%	
Lead Coupon @ 100 hrs, % wt. change**	%	
EOT Al Strip Varnish (CRC Manual 14)	-	
EOT Sludge	-	

\*\*% Change: Negative value = weight loss. Positive value = weight gain

<b>Test Operating Conditions</b>	
Test Temperature, °C	
Air Flow Rate, mL/min	

<b>Comments</b>

**DEXRON® Aluminum Beaker Oxidation Test**  
**Chemical Analysis Data**  
**Form 3**

Formulation Code	
Test Number	

Date	Test Hours	Pentane Insolubles Weight %	Acid Number (D664 – 1g) Mg KOH/g		Acid Change		Infrared Differential ABS/cm	Viscosity (D445) @ 40°C cst	Viscosity Change %
			Inflection	Buffer	Inflection	Buffer			
	0								
	50								
	100								
	150								
	200								
	250								
	300								

Additional 0 hour Chemical Analysis	
Viscosity (D445) @ 100°C, cSt	
Acid Number (D664), mg KOH/g-Inflection*	
Acid Number (D664), mg KOH/g-Buffer*	
Chlorine Content (D6443), ppm	
Nitrogen Content (D4629), ppm	
Sulfur Content (D5185), wt. %	

\* D664 conducted on 5 gram sample

Additional Data	Results
EOT Viscosity (D2983) @ -40°C, Cp	
Copper Strip Corrosion (D130) @ 50 hrs.	
Copper Strip Corrosion (D130) @ EOT	
Initial Weight of Beaker, g (Wbi)	
Initial Weight of Oil, g (Wi)	
Total Aliquot Sample Weight, g (Wm)	
Beaker and Oil Weight, g (Wbf) @ EOT	
Calculated Percent Weight Loss (Wi+Wbi-Wa-Wbf)x100	

**DEXRON® Aluminum Beaker Oxidation Test**  
**ICP Data**  
**Form 4**

Formulation Code	
Test Number	

<b>ICP Elemental Analysis (D5185), ppm<sup>A</sup></b>			
Element	New Oil	100 hour	EOT
Aluminum (Al)			
Antimony (Sb)			
Barium (Ba)			
Boron (B)			
Cadmium (Cd)			
Calcium (Ca)			
Chromium (Cr)			
Copper (Cu)			
Iron (Fe)			
Lead (Pb)			
Magnesium (Mg)			
Manganese (Mn)			
Molybdenum (Mo)			
Nickel (Ni)			
Phosphorus (P)			
Potassium (K)			
Silicon (Si)			
Silver (Ag)			
Sodium (Na)			
Tin (Sn)			
Titanium (Ti)			
Vanadium (V)			
Zinc (Zn)			

<sup>A</sup>Report 0 for values below the measurement threshold of the instrument. Do not use less than (“<”) symbol.

**DEXRON® Aluminum Beaker Oxidation Test**  
**FTIR Plot**  
**Form 5**

Formulation Code	
Test Number	