

DEXRON® GM 6L80 Cycling Test**Report Form****Form 1****Version**

| Formulation Code | | | | | | | |
|-------------------------|-------------|--------------|-------|-------|--------|-----|------------|
| Formulation Code | | | | | | | |
| SPONID | SponsorCode | Modification | Blend | Count | Method | Lab | Instrument |
| | | | | | | | |

| Blended Sample Testing Information^A | | | |
|---|--|------------------|--|
| Candidate Percentage | | Other Percentage | |
| Other Fluid ID | | | |

^A If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and "None" for Blend Fluid ID.

| Test Identification | | | |
|----------------------------|--|------------|--|
| Sponsor | | | |
| Sponsor In-House Number | | | |
| Lab In-House Number | | | |
| Alternate Code | | | |
| Test Number ^B | | | |
| Instrument | | Run Number | |
| Start Date | | Start Time | |
| EOT Date | | EOT Time | |

^B Test Number = Instrument – Run Number

| Test Validity Statement | |
|--|--|
| This test has been conducted in a valid manner – YES or NO | |
| | |
| Test Laboratory | |
| Signature | |
| Typed Name | |
| Title | |

DEXRON® GM 6L80 Cycling Test
Pass/Fail Results
Form 2

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

| Pass/Fail Results | | |
|---|--------|---------------------|
| Parameter | Unit | Result ^A |
| Total Acid Number Increase | | |
| Used Fluid Viscosity @ 100°C | cSt | |
| Used Fluid Viscosity @ -20°C | cP | |
| Used Fluid Viscosity @ -40°C | cP | |
| Pentane Insolubles (D893 Procedure B) | % | |
| Toluene Insolubles (D893 Procedure B) | % | |
| Insoluble Resins (D893 Procedure B) | % | |
| ATF expulsion from vent? | YES/NO | |
| 3-4 Shift NVH Count | | |
| Clutch 1-2-3-4 Wear vs Reference Fluid | mm | |
| Clutch 2-6 Wear vs Reference Fluid | mm | |
| Clutch 3-5-R Wear vs Reference Fluid | mm | |
| Clutch 4-5-6 Wear vs Reference Fluid | mm | |
| Test Fluid analytical results are shown on Form 3 | | |
| Reference Fluid analytical results are shown on Form 4 | | |
| Test Fluid Shift Time results are shown on Form 5 | | |
| Reference Fluid Shift Time results are shown on Form 6 | | |
| Friction material wear measurements are shown on Form 7 | | |
| Test Fluid Transmission parts condition is shown on Form 8 | | |
| Reference Fluid Transmission parts condition is shown on Form 9 | | |

^AReport 0 for values below the measurement threshold of the instrument. Do not use less than ("<") symbol.

| Test Operating Conditions | |
|---------------------------|--|
| Total Test Cycles | |

| Comments |
|----------|
| |
| |
| |
| |
| |

DEXRON® GM 6L80 Cycling Test
Test Fluid Analytical Data
Form 3

| | | | | | | | | | |
|------------------|--|--|--|--|--|--|--|--|--|
| Formulation Code | | | | | | | | | |
| Test Number | | | | | | | | | |

| | CYCLES | Test Fluid | | | | | | | | | EOT |
|--------------|-------------------|------------|-------|--------|--------|--------|--------|--------|--------|--------|-----|
| | | 0 | 8,000 | 16,000 | 24,000 | 32,000 | 40,000 | 48,000 | 56,000 | 64,000 | |
| D2983 | Brookfield | | | | | | | | | | |
| | -20°C | | | | | | | | | | |
| | -40°C | | | | | | | | | | |
| D445 | Viscosity | | | | | | | | | | |
| | 100°C | | | | | | | | | | |
| | 40°C | | | | | | | | | | |
| D5185 | ICPA ^A | | | | | | | | | | |
| | Al [ppm] | | | | | | | | | | |
| | Cu [ppm] | | | | | | | | | | |
| | Fe [ppm] | | | | | | | | | | |
| | Pb [ppm] | | | | | | | | | | |
| D664 | TAN | | | | | | | | | | |
| TAN Increase | | 0.00 | | | | | | | | | |
| D893B | Pentane Ins | | | | | | | | | | |
| D893B | Toluene Ins | | | | | | | | | | |
| D893B | Ins Resins | | | | | | | | | | |
| E168 | Diff IR | 0.00 | | | | | | | | | |

^AReport 0 for values below the measurement threshold of the instrument. Do not use less than ("<") symbol.

DEXRON® GM 6L80 Cycling Test
Reference Fluid Analytical Data
Form 4

| | | | | | | | | |
|------------------|--|--|--|--|--|--|--|--|
| Formulation Code | | | | | | | | |
| Test Number | | | | | | | | |

| | | Reference Fluid | | | | | | | | EOT |
|------------------------|------|-----------------|--------|--------|--------|--------|--------|--------|--------|-----|
| CYCLES | 0 | 8,000 | 16,000 | 24,000 | 32,000 | 40,000 | 48,000 | 56,000 | 64,000 | |
| D2983 Brookfield | | | | | | | | | | |
| -20°C | | | | | | | | | | |
| -40°C | | | | | | | | | | |
| D445 Viscosity | | | | | | | | | | |
| 100°C | | | | | | | | | | |
| 40°C | | | | | | | | | | |
| D5185 ICP ^A | | | | | | | | | | |
| Al [ppm] | | | | | | | | | | |
| Cu [ppm] | | | | | | | | | | |
| Fe [ppm] | | | | | | | | | | |
| Pb [ppm] | | | | | | | | | | |
| D664 TAN | | | | | | | | | | |
| TAN Increase | 0.00 | | | | | | | | | |
| D893B Pentane Ins | | | | | | | | | | |
| D893B Toluene Ins | | | | | | | | | | |
| D893B Ins Resins | | | | | | | | | | |
| E168 Diff IR | 0.00 | | | | | | | | | |

^AReport 0 for values below the measurement threshold of the instrument. Do not use less than ("<") symbol.

DEXRON® GM 6L80 Cycling Test
Test Fluid Shift Lock Up Time Results
Form 5

| | | | | | |
|------------------|--|--|--|--|--|
| Formulation Code | | | | | |
| Test Number | | | | | |

| | | Test Fluid | | | | |
|-----------|--------|------------|--------|--------|--------|--------|
| Lock Ups | 200 | 1,000 | 2,000 | 4,000 | 6,000 | 8,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 10,000 | 12,000 | 14,000 | 16,000 | 18,000 | 20,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 22,000 | 24,000 | 26,000 | 28,000 | 30,000 | 32,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 34,000 | 36,000 | 38,000 | 40,000 | 42,000 | 44,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 46,000 | 48,000 | 50,000 | 52,000 | 54,000 | 56,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 58,000 | 60,000 | 62,000 | 64,000 | EOT | |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |

DEXRON® GM 6L80 Cycling Test
Reference Fluid Shift Lock Up Time Results
Form 6

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

| Reference Fluid | | | | | | |
|-----------------|--------|--------|--------|--------|--------|--------|
| Lock Ups | 200 | 1,000 | 2,000 | 4,000 | 6,000 | 8,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 10,000 | 12,000 | 14,000 | 16,000 | 18,000 | 20,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 22,000 | 24,000 | 26,000 | 28,000 | 30,000 | 32,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 34,000 | 36,000 | 38,000 | 40,000 | 42,000 | 44,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 46,000 | 48,000 | 50,000 | 52,000 | 54,000 | 56,000 |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |
| Lock Ups | 58,000 | 60,000 | 62,000 | 64,000 | EOT | |
| 1-2 Shift | | | | | | |
| 2-3 Shift | | | | | | |
| 3-4 Shift | | | | | | |
| 4-5 Shift | | | | | | |
| 5-6 Shift | | | | | | |

DEXRON® GM 6L80 Cycling Test
Friction Materials Measurements
Form 7

| | | | |
|------------------|--|--|--|
| Formulation Code | | | |
| Test Number | | | |

| Test Fluid Parts Measurements | | | | |
|--------------------------------------|---------|-----|-------|-------|
| New Parts Measurements, mm | | | | |
| Clutch | 1-2-3-4 | 2-6 | 3-5-R | 4-5-6 |
| 0° | | | | |
| 90° | | | | |
| 180° | | | | |
| 270° | | | | |
| Average | | | | |
| EOT Parts Measurements, mm | | | | |
| Clutch | 1-2-3-4 | 2-6 | 3-5-R | 4-5-6 |
| 0° | | | | |
| 90° | | | | |
| 180° | | | | |
| 270° | | | | |
| Average | | | | |
| Measurement Changes (New – EOT), mm | | | | |
| Clutch | 1-2-3-4 | 2-6 | 3-5-R | 4-5-6 |
| 0° | | | | |
| 90° | | | | |
| 180° | | | | |
| 270° | | | | |
| Average | | | | |

| Reference Fluid Parts Measurements | | | | |
|---|---------|-----|-------|-------|
| New Parts Measurements, mm | | | | |
| Clutch | 1-2-3-4 | 2-6 | 3-5-R | 4-5-6 |
| 0° | | | | |
| 90° | | | | |
| 180° | | | | |
| 270° | | | | |
| Average | | | | |
| EOT Parts Measurements. Mm | | | | |
| Clutch | 1-2-3-4 | 2-6 | 3-5-R | 4-5-6 |
| 0° | | | | |
| 90° | | | | |
| 180° | | | | |
| 270° | | | | |
| Average | | | | |
| Measurement Changes (New – EOT), mm | | | | |
| Clutch | 1-2-3-4 | 2-6 | 3-5-R | 4-5-6 |
| 0° | | | | |
| 90° | | | | |
| 180° | | | | |
| 270° | | | | |
| Average | | | | |

| Reference Fluid Delta vs. Test Fluid Delta Parts Measurements | | | | |
|--|---------|-----|-------|-------|
| Reference Fluid Delta Average – Test Fluid Delta Average, mm | | | | |
| Clutch | 1-2-3-4 | 2-6 | 3-5-R | 4-5-6 |
| Average | | | | |

**DEXRON® GM 6L80 Cycling Test
Inspection Report – Test Fluid
Form 8**

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

**DEXRON® GM 6L80 Cycling Test
Inspection Report – Reference Fluid
Form 9**

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

DEXRON® GM 6L80 Cycling Test
Test Report Placeholder Form
Form 10

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

Append the complete test report PDF
to these forms, in place of this page.