

**DEXRON® Electrical Conductivity ASTM D2624 - Modified
Report Form
Form 1
Version**

| Formulation Code | | | | | | | |
|------------------|-------------|--------------|-------|-------|----------|-----|-----------|
| Formulation Code | | | | | | | |
| SPONID | SponsorCode | Modification | Blend | Count | TestType | Lab | Test Cell |
| | | | | | | | |

| Blended Sample Testing Information ^A | | | |
|---|--|------------------|--|
| Candidate Percentage | | Other Percentage | |
| Other Fluid ID | | | |

^A If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and "None" for Blend Fluid ID.

| Test Identification | | | |
|--------------------------|--|------------|--|
| Sponsor | | | |
| Sponsor In-House Number | | | |
| Lab In-House Number | | | |
| Alternate Code | | | |
| Test Number ^B | | | |
| Test Cell | | Run Number | |
| Start Date | | Start Time | |
| EOT Date | | EOT Time | |

^B Test Number = Test Cell (conductivity cell) – Run Number

| Test Validity Statement | |
|--|--|
| This test has been conducted in a valid manner – YES or NO | |
| | |
| Test Laboratory | |
| Signature | |
| Typed Name | |
| Title | |

DEXRON® Electrical Conductivity Test – ASTM D2624 - Modified
Pass/Fail Results
Form 2

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

| Pass/Fail Results | | |
|--------------------------|----------------------------|------|
| Temperature (°C) | Specific Resistance (pS/m) | |
| | New | Used |
| 22 | | |
| 30 | | |
| 40 | | |
| 50 | | |
| 60 | | |
| 70 | | |
| 100 | | |
| 120 | | |
| 150 | | |

| Additional Test Identification Information | | |
|---|-----|------|
| Item | New | Used |
| Used Fluid Conditioning ^A | | |
| Measurement Start Date | | |
| Measurement Start Time | | |
| Measurement EOT Date | | |
| Measurement EOT Time | | |

| | |
|--|--------------------------------------|
| ^A Used Fluid Condition Values | Used Fluid Condition Description |
| AABOT | After Aluminum Beaker Oxidation Test |
| ACYC | After Cycling Test |

DEXRON® Electrical Conductivity – ASTM D2624 - Modified

Resistance vs Temperature Plot (New vs Used)

Form 3

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |