

**DEXRON® GM Three (3) Day Wear Test  
Report Form  
Form 1  
Version**

Formulation Code							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Method	Count	Lab	Instrument

Blended Sample Testing Information <sup>A</sup>			
Candidate Percentage			Other Percentage
Other Fluid ID			

<sup>A</sup> If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and "None" for Blend Fluid ID.

Test Identification			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number <sup>B</sup>			
Instrument		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	

<sup>B</sup> Test Number = Instrument – Run Number

Test Validity Statement	
This test has been conducted in a valid manner – YES or NO	
Test Laboratory	
Signature	
Typed Name	
Title	

**DEXRON® GM Three (3) Day Wear Test  
Test Operational Details & Comments  
Form 2**

Formulation Code	
Test Number	

<b>Test Fluid Condition before Testing</b>	
Test Fluid Condition <sup>A</sup>	
<i><sup>A</sup> Fluid Condition Values</i>	<i>Description</i>
<i>NEW</i>	<i>New Fluid</i>
<i>H2O</i>	<i>New Fluid treated with 1000 ppm Water, per GM procedure</i>

<b>Test Operational Details</b>	
Clutch Plate Type	
Friction Material ID, mm	
Friction Material OD, mm	
Groove %	
Groove Pattern	
Effective Friction Radius, mm	
Apply Piston Area, mm <sup>2</sup>	
Friction Material Type	
Friction Material Batch	
Steel Separator Type	
Steel Separator Batch	
Test Machine Type	

<b>Comments</b>

**DEXRON® GM Three (3) Day Wear Test  
Clutch Pack Plate Thickness Measurements  
Form 3**

Formulation Code	
Test Number	

<b>Pre Test (New), mm</b>			
Position	Front Steel	Rear Steel	Friction Disc
12:00			
3:00			
6:00			
9:00			
Average			

<b>Post Break In, mm</b>			
Position	Front Steel	Rear Steel	Friction Disc
12:00			
3:00			
6:00			
9:00			
Average			

<b>Post Test, mm</b>			
Position	Front Steel	Rear Steel	Friction Disc
12:00			
3:00			
6:00			
9:00			
Average			

<b>(Pre Test) – (Post Break In), mm</b>			
Position	Front Steel	Rear Steel	Friction Disc
12:00			
3:00			
6:00			
9:00			
Average			

<b>(Post Break In) - (Post Test), mm</b>			
Position	Front Steel	Rear Steel	Friction Disc
12:00			
3:00			
6:00			
9:00			
Average			

<b>(Pre Test) - (Post Test), mm</b>			
Position	Front Steel	Rear Steel	Friction Disc
12:00			
3:00			
6:00			
9:00			
Average			

**DEXRON® GM Three (3) Day Wear Test  
Test Report Placeholder Form  
Form 4**

Formulation Code	
Test Number	

Append the complete test report PDF to these forms, in place of this page.