

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified
Report Forms
Form 1**

| Formulation Code | | | | | | | |
|------------------|-------------|--------------|-------|--------|-------|-----|----------|
| Formulation Code | | | | | | | |
| SPONID | SponsorCode | Modification | Blend | Method | Count | Lab | Test Rig |
| | | | | | | | |

| Blended Sample Testing Information ^A | | | |
|---|--|--|------------------|
| Candidate Percentage | | | Other Percentage |
| Other Fluid ID | | | |

^A If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and “None” for Blend Fluid ID.

| Test Identification | | | |
|--------------------------|--|------------|--|
| Sponsor | | | |
| Sponsor In-House Number | | | |
| Lab In-House Number | | | |
| Alternate Code | | | |
| Test Number ^B | | | |
| Test Rig | | Run Number | |
| Start Date | | Start Time | |
| EOT Date | | EOT Time | |

^B Test Number = Test Rig– Run Number

| Test Validity Statement | |
|--|--|
| This test has been conducted in a valid manner – YES or NO | |
| | |
| Test Laboratory | |
| Signature | |
| Typed Name | |
| Title | |

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified
Pass/Fail Results
Form 2**

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

| Pass/Fail Result | |
|--|--|
| EOT Kinematic Viscosity @ 100°C - cSt | |
| EOT Kinematic Viscosity Decrease @ EOT - % | |
| (Base Oil Viscosity + EOT Viscosity)/2 - cSt | |

| Test Conditions | |
|-----------------------------|--|
| Revolutions | |
| Test Length - h | |
| Test Fluid Temperature - °C | |

| Viscosity Measurements | | | |
|-------------------------------------|-----------------|-----------------------|------------------------|
| | Viscosity - cSt | Viscosity Delta - cSt | Viscosity Decrease - % |
| Initial Kinematic Viscosity @ 100°C | | | |
| EOT Kinematic Viscosity @ 100°C | | | |
| Base Oil Viscosity @ 100°C | | | |

| Comments |
|-----------------|
| |
| |
| |
| |
| |
| |