

DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified
Report Forms
Form 1

Formulation Code							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Method	Count	Lab	Test Rig

Blended Sample Testing Information ^A		
Candidate Percentage		Other Percentage
Other Fluid ID		

^A If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and "None" for Blend Fluid ID.

Test Identification			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number ^B			
Test Rig		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	

^B Test Number = Test Rig– Run Number

Test Validity Statement	
This test has been conducted in a valid manner – YES or NO	
Test Laboratory	
Signature	
Typed Name	
Title	

DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified
Pass/Fail Results
Form 2

Formulation Code	
Test Number	

Test Condition Summary	
Test Fluid Conditions ^A	
^A Fluid Condition Values	Description
40	~40h test duration; 3,480,000 cycles
100	~100h test duration; 8,700,000 cycles

Pass/Fail Result	
EOT Kinematic Viscosity @ 100°C - cSt	
EOT Kinematic Viscosity Decrease @ EOT - %	
(Base Oil Viscosity + EOT Viscosity)/2 - cSt	

Specific Test Conditions	
Revolutions	
Test Length - h	
Test Fluid Temperature - °C	

Viscosity Measurements			
	Viscosity - cSt	Viscosity Delta - cSt	Viscosity Decrease - %
Initial Kinematic Viscosity @ 100°C			
EOT Kinematic Viscosity @ 100°C			
Base Oil Viscosity @ 100°C			

Comments