

**General Motors RNT – Valvetrain Wear Test  
For dexos®  
Final Report Cover Sheet**

**Form 1**

Version:

Conducted For

	V = Valid
	I = Invalid

	NR = Non-reference oil
	RO = Reference oil

<b>Test Number</b>			
Test Stand		Stand Run	
Oil Code			
Formulation Stand Code			
SAE Viscosity Grade			
Date Started		Time Started	
Date Completed		Time Completed	
Test Length		Total Downtime	
Alternate Codes:			

<p>In my opinion this test _____ has been conducted in a valid manner in accordance with the OPEL GMPTE-T test procedure and the appropriate amendments. The remarks included in this report describe anomalies associated with this test.</p>
--

Submitted By:

\_\_\_\_\_ Testing Laboratory

\_\_\_\_\_ Signature

\_\_\_\_\_ Typed Name

\_\_\_\_\_ Title

**General Motors RNT – Valvetrain Wear Test  
For dexos®**

**Form 2**

**Table of Contents**

1.	Title / Validity Declaration Page	Form 1
2.	Table of Contents / Introduction	Form 2
3.	Results Summary	Form 3
4.	Camshaft Lobe and Tappet Wear: Tables and Graphs	Forms 4 - 6
5.	Downtime Occurrences	Form 7
6.	Test Comments	Form 8

**Introduction**

- The activation has been done on all tappets as well as on the inlet camshaft (cam 2, 5 and 7) using different nuclides.
- The wear speed was calculated based on condition that the wear-rate is constant over the whole surface of activation.
- The engine has been operated under the different test conditions until constant wear rate was observed (15 h break-in + 35 h reference 1).

**General Motors RNT – Valvetrain Wear Test  
For dexos®**

**Form 3  
Results Summary**

Lab:		Oil Code:	
Stand:		Test No:	
Laboratory Oil Code:			
Formulation/Stand Code:			

Test Engine		Engine Number	
Test Fuel			

	<b>Max. Cam Wear (nm/h)</b>	<b>Max. Tappet Wear (nm/h)</b>
1. Function of speed (n= 1200....6400 rpm)		
2. 'Saw tooth' (1000-6000 rpm)		
3. Pitting Test (LL-VL)		
4. Function of oil temperature (T <sub>OIL</sub> = 130....140 °C)		

**General Motors RNT – Valvetrain Wear Test  
For dexos®**

**Form 4  
Function of Speed**

Lab:		Oil Code:	
Stand:		Test No:	
Laboratory Oil Code:			
Formulation/Stand Code:			

**Wear Rate ‘Camshaft’**

**Wear Rate ‘Tappets’**

Parameter	Units	Min	Max	Average
Wear Rate Camshaft	nm/h			
Wear Rate Tappets	nm/h			

**General Motors RNT – Valvetrain Wear Test  
For dexos®**

**Form 5  
Function of Oil Temperature**

Lab:		Oil Code:	
Stand:		Test No:	
Laboratory Oil Code:			
Formulation/Stand Code:			

**Wear Rate ‘Camshaft’**

**Wear Rate ‘Tappets’**

Parameter	Units	Min	Max	Average
Wear Rate Camshaft	nm/h			
Wear Rate Tappets	nm/h			

**General Motors RNT – Valvetrain Wear Test  
For dexos®**

**Form 6  
Test parts: Reference/ ‘Saw tooth’/Pitting**

Lab:		Oil Code:	
Stand:		Test No:	
Laboratory Oil Code:			
Formulation/Stand Code:			

**Wear Rate ‘Camshaft’**

**Wear Rate ‘Tappets’**

Ref 1: Reference run (part of the run-in procedure)  
SA: Alternating speed (1000 and 6000 rpm; 1 minute frequency), part load  
PI: Alternating: idle – 5000 rpm/WOT  
Ref 2: Reference run after test

**General Motors RNT – Valvetrain Wear Test  
For dexos®**

**Form 7  
Downtime Occurrences**

Lab:		Oil Code:	
Stand:		Test No:	
Laboratory Oil Code:			
Formulation/Stand Code:			

Number of Downtime Occurrences			
Test Hours	Date	Downtime	Reasons
			<b>Total Downtime (hours)</b>

